



- TECHICAL REQUIREMENTS
1. CANTILEVER STRENGTH: 1000# [4.55KN]
 2. TENSILE STRENGTH: 2000# [9.1KN]
 3. TORSION STRENGTH: 2500"#[0.29KN.M]
 4. COMPRESSION STRENGTH: 20000# [89KN]
 5. NEMA. VOLTAGE RATING: 4.8KV
 6. 50 HERTZ WITHSTAND-DRY: 19KV
 7. 50 HERTZ WITHSTAND-DEW: 15KV
 8. IMPULSE WITHSTAND: 60KV
 9. MINIMUM CREPAGE DISTANCE: 5" [127mm]
 10. GLAZE: ANSI 70 LIGHT GREY
 11. APPLICABLE STANDARD: ANSI C29.10-1989

ePi EGER PRODUCTS, INC.

REVISIONS:

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
EGER PRODUCTS, INC.. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
EGER PRODUCTS INC. IS
PROHIBITED.

DATE: 8/1/2014
SCALE: NTS
DRAWN BY: E. GREEN
APPROVED BY:

CUSTOMER:
A20-1
DWG. INDOOR BUS SUPPORT
MATERIAL: