



TECHNICAL REQUIREMENTS

1. CANTILEVER STRENGTH: 1500# [6.8KN]
2. TENSILE STRENGTH: 3000# [13.7KN]
3. TORSION STRENGTH: 3500" # [0.41KN.M]
4. COMPRESSION STRENGTH: 20000# [91KN]
5. NEMA VOLTAGE RATING: 7.2KV
6. 50 HERTZ WITHSTAND-DRY: 26KV
7. 50 HERTZ WITHSTAND-DEW: 24KV
8. IMPULSE WITHSTAND: 75KV
9. GLAZE: ANSI 70 LIGHT GREY
10. APPLICABLE STANDARD: ANSI C29.10-1989



EGER PRODUCTS, INC.

REVISIONS:

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 EGER PRODUCTS, INC. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
 EGER PRODUCTS INC. IS
 PROHIBITED.

DATE: 8/1/2014

CUSTOMER:

SCALE: NTS

A20-2

DRAWN BY: E. GREEN

DWG. INDOOR BUS SUPPORT

APPROVED BY:

MATERIAL: