



TECHICAL REIREMENTS

1. CANTILEVER STRENGTH: 1250# [5.69KN]
2. TENSILE STRENGTH: 3000# [13.7KN]
3. TORSION STRENGTH: 3500" # [0.41KN.M]
4. COMPRESSION STRENGTH: 20000# [91KN]
5. NEMA VOLTAGE RATING: 13.2KV
6. 50 HERTZ WITHSTAND-DRY: 36KV
7. 50 HERTZ WITHSTAND-DEW: 26KV
8. IMPULSE WITHSTAND: 95KV
9. GLAZE: ANSI 70 LIGHT GREY
10. APPLICABLE STANDARD: ANSI C29.10-1989



EGER PRODUCTS, INC.

REVISIONS:

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
EGER PRODUCTS, INC.. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
EGER PRODUCTS INC. IS  
PROHIBITED.

DATE: 8/1/2014

CUSTOMER:

SCALE: NTS

A20-3

DRAWN BY: E. GREEN

DWG. INDOOR BUS SUPPORT

APPROVED BY:

MATERIAL: