



CATALOG NUMBER	USUAL LINE VOLTAGE	RADIO INFLUENCE TEST VOLTAGE Rms to Ground	MAXIMUM RIV Microvolts to 1000 kc	CANTILEVER STRENGTH
U4327 G	27 KV	20	50	1500 LBS.

CATALOG NUMBER	LEAKAGE DISTANCE	DRY ARCHING DISTANCE	LOW FREQUENCY FLASHOVER — kV	IMPULSE FLASHOVER — kV	WEIGHT PER 100
U4327 G	15"	7 3/4"	95 DRY 65 WET	135 POSITIVE 190 NEGATIVE	1040 LBS.

THE ABOVE LINE POST INSULATOR IS OFFERED IN A "SKY GRAY" GLAZE. (ANSI - 70)  
 FOR CHOCOLATE GLAZE CHANGE THE SUFFIX IN THE CATALOG NUMBER FROM "G" TO "B".  
 LINE POST STUDS ARE FURNISHED SEPARATELY. PLEASE REFER TO OUR HARDWARE SECTION FOR SELECTION.



EGER PRODUCTS, INC.

**REVISIONS:**

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS  
 DRAWING IS THE SOLE PROPERTY OF  
 EGER PRODUCTS, INC.. ANY  
 REPRODUCTION IN PART OR AS A WHOLE  
 WITHOUT THE WRITTEN PERMISSION OF  
 EGER PRODUCTS INC. IS  
 PROHIBITED.

DATE: 8/1/2014

CUSTOMER:

SCALE: NTS

NE POST INSULATOR "F" NECK TYPE

DRAWN BY: E. GREEN

DWG. NE POST INSULATOR "F" NECK TYPE

APPROVED BY:

MATERIAL: